


XG1008AC/XG1012AC

Scissor lifts

FEATURES

PRODUCTIVITY

- 2 front driving wheels
- 25% theoretical gradeability
- Battery charge indicator and diagnostic display
- Manual platform lowering valve
- Both platform and ground control panel with emergency stop button
- Front wheel multi-disc brakes
- Manual brake release
- Solid non-marking tires
- Mobile pothole protection
- Tilt alarm
- Hourmeter record
- Lift and lower alarm
- Horn
- Dual flashing beacons
- Drive alarm
- Overload alarm



OPTIONS

- Platform working light
- Air-line to platform
- AC power to the platform
- Lithium battery

Item	Unit	XG1008AC	XG1012AC
Lift capacity	kg	230	450
Lift capacity of auxiliary platform	kg	115	115
Occupant Capacity	-	2	2
Working height	m	10	10
Platform height	m	8	8
Length of auxiliary platform	mm	900	900
Ground clearance(Pot hole protector – raised/lowered)	mm	100/20	110/20
Turning radius(inside/outside)	m	0/2.3	0/2.3
Drive motor	kW	0.87	0.87
Lift motor	kW	3.3	3.3
Drive speed-full retracted	km/h	4.0	4.0
Drive speed-full extended	km/h	0.8	0.8
Lift/Lower time	s	29~40/34~45	29~40/49~60
Gradeability	%	25	25
Tilt alarm(side/forward and backward)	°	1.5/3	1.5/3
Batteries	V/Ah	4 x 6/280	4 x 6/280
Charger	V/A	24/30	24/30
Tires	-	381 x 127	381 x 127
Weight	kg	2260	2680
a Length(without ladder)	mm	2477(2280)	2477(2267)
b Width	mm	810	1170
c Height(platform folded)	mm	2335(2005)	2335(2005)
d x e Platform size(Length x Width)	mm	2270 x 810	2270 x 1120
f Wheelbase	mm	1877	1877